

**AISI 316 RIPARABILE DALL'ALTO**

Accumulatori idropneumatici a sacca con corpo in acciaio inossidabile AISI 316L.

**Caratteristiche Tecniche:**

Pressione massima di lavoro (PS): 220 bar

Pressione massima di precarica: 145 bar

Pressione di prova (PT): PS x 1,43

Corpo: in acciaio inox AISI 316L

Metodologia costruttiva: tre componenti distinti uniti da una speciale filettatura che sottoposta a pressioni dinamiche tende ad autobloccarsi

Sacca: differenti tipologie in relazione al fluido utilizzato:

- Perbunan (NBR)
- Butil
- Nitrile (NBR)
- Nitrile HNBR
- EPDM
- Viton

Montaggio: posizione verticale; valvola fluido verso l'alto

Rapporto di compressione:

- consigliato: P2/P0 = 2.5
- massimo: P2/P0 = 4

Vita meccanica: il numero di cicli è inversamente proporzionale all'aumento del rapporto di compressione.

Per utilizzo come antipulsazione la pressione di precarica deve rientrare tra il 60% e l' 80% della pressione di lavoro in considerazione anche del valore della temperatura.

Garanzia: vedi pagina dedicata

Parti di ricambio: vedi pagina dedicata

Disponibile:

- esecuzioni flangiate a richiesta
- Corpo in ALLOY 20 / HASTELLOY



Conforme a:

- 97/23/CE - PED
- 94/9/CE - ATEX Group II Cat 2
- ASME VIII° div.1 STAMP
- GOST-R (Russia)
- SELO (China)



**AISI316 TOP REPAIRABLE**

Bladder type hydropneumatic accumulators with body in AISI 316L stainless steel.

**Technical features :**

Maximum working pressure (PS): 220 bar

Maximum preload pressure: 145 bar

Test pressure (PT): PS x 1,43

Body : in AISI 316L Stainless Steel

Construction methods : three different parts united with a special threading that under conditions of dynamic pressure tends to self-block

Bladder : differently type due to the fluid utilized :

- Perbunan (NBR)
- Butil
- Nitrile (NBR)
- Nitrile HNBR
- EPDM
- Viton

Installation position: vertical position, nitrogen valve upward

Compression Ratio:

- recommended: P2/P0 = 2.5
- maximum: P2/P0 = 4

Mechanical life: the number of the cycles is inversely proportional to the increase of the compression ratio.

To be used as antipulsation dampener, the precharged pressure should be between 60% and 80% of the working pressure depending also to the temperature value.

Warranty: see dedicated page

Spare parts: see dedicated page


Available:

- flanged execution on requests
- ALLOY 20 / HASTELLOY body



According to:

- 97/23/CE - PED
- 94/9/CE - ATEX Group II Cat 2
- ASME VIII° div.1 STAMP
- GOST-R (Russia)
- SELO (China)



Tipo	Pressione Max	Precarica N2 Max	Pressione Prova	Volume Azoto	H	D	C	B	Connessione Idraulica	Peso
Type	Max Pressure	Max N2 Preload	Test pressure	Nitrogen Volume					Hydraulic Connection	Weight
	bar	bar	bar	Lt	mm	mm	mm	mm		Kg
ACSX 10	220	145	315	10	450	250	36	70	2" BSP	60
ACSX 20				20	735					99.5
ACSX 25				25	885					120
ACSX 35				35	1265					173
ACSX 50				50	1750					240