

-10°C ÷ 50°C

Compressed air, vacuum and fluids suitable with construction materials

Material: Single layer transparent PVC

FEATURES

- Hardness:
  75 Shore A
- Breaking load at 23°C:
  ≥ 13,5 N/mm²
- Elongation at break at 23°C:
  ≥ 350 %
- Density (at 23°C):
  1,22 g/cm³

SILICONE FREE

Products in compliance with EC Regulation 1907/2006

RoHS3

Products in compliance with the directive EU 2015/863

PVC

Single layer transparent PVC tube



CODE	Ø IDxOD	THICKNESS (mm)	MIN. BENDING RADIUS (mm)	g/m	Q.TY FOR ROLL (mt)
PVC0406	4x6	1	32	19	200
PVC0407	4x7	1,5	32	32	200
PVC0609	6x9	1,5	48	45	100
PVC0710	7x10	1,5	56	50	100
PVC0812	8x12	2	64	75	100
PVC1014	10x14	2	80	92	100
PVC1217	12x17	2,5	120	140	100
PVC1419	14x19	2,5	140	155	100
PVC1622	16x22	3	160	215	50
PVC1824	18x24	3	175	240	50
PVC2027	20x27	3,5	200	310	50
PVC2533	25x33	4	250	440	50

Sizes Ø IDxOD	∅ Transparent
4x6	PVC0406
4x7	PVC0407
6x9	PVC0609
7x10	PVC0710
8x12	PVC0812
10x14	PVC1014
12x17	PVC1217
14x19	PVC1419
16x22	PVC1622
18x24	PVC1824
20x27	PVC2027
25x33	PVC2533

drawings and technical data are not binding & can be changed without notice