

## TUBO POLIURETANO A BASE POLIESTERE

### polyurethane tube on polyester basis

#### DATI TECNICI

Fluidi applicabili	Aria
Pressione negativa	-29,5 in Hg / -750 mmHG (-750 Torr)
Temperatura d'esercizio	da 32° a 140 °F / da 0 a 60°C
Caratteristiche	Il tubo in poliuretano a base poliestere ha un'alta flessibilità a basse temperature ed una buona resistenza all'usura ed alle sostanze chimiche.

Prodotti conformi alla direttiva 2002/95/EC **RoHS**

#### Technical specifications

<i>applicable fluids</i>	<i>air</i>
<i>negative pressure</i>	<i>-29,5 in Hg / -750 mmHG (-750 Torr)</i>
<i>working temperature</i>	<i>from 32° to 140 °F / from 0°C to 60°C</i>
<i>advantages</i>	<i>polyurethane tube on polyester basis has a high flexibility at low temperatures and a good tolerance to wear and tear &amp; chemicals</i>

products in conformity with the directive 2002/95/EC **RoHS**

I dati tecnici e le quote non sono vincolanti • drawings and technical data are not binding

tubo poliuretano a base poliestere • polyurethane tube on polyester basis

## PUES



CODE	Misure (O.D. x I.D.)  sizes (O.D. x I.D.)	Tolleranza Ø Esterno Tubo (mm)  tolerance Ø outer tube (mm)	Raggio di Curvatura min. a 23°C (mm)  min. bending radius at 23°C (mm)	Pressione d'Esercizio a 23°C (Bar)  working pressure at 23°C (bar)	Pressione di Scoppio a 23°C (Bar)  Burst pressure at 23°C (bar)	Durezza  hardness	Colori Disponibili  available colours	Peso g/mt  weight g/mt	Q.tà per matassa  q.ty for roll
PUES 0302	3x2	+0,1-0,1	8	10,0	30,0		●	7,5	100mt.
PUES 0425	4x2,5	+0,1-0,1	12	10,0	30,0		●●●●●●●●	9,0	100mt.
PUES 0604	6x4	+0,1-0,1	15	8,5	25,5		●●●●●●●●	18,0	100mt.
PUES 0805	8x5	+0,1-0,1	20	8,5	25,5		●●●●●●●●	35,0	100mt.
PUES 0855	8x5,5	+0,1-0,1	20	8,5	25,5		●●●●●●●●	38,0	100mt.
PUES 1065	10x6,5	+0,15-0,15	25	8,5	25,5		●●●●●●●●	55,0	100mt.
PUES 1007	10x7	+0,15-0,15	25	8,0	24,0		●●●●●●●●	49,0	100mt.
PUES 1208	12x8	+0,15-0,15	35	8,5	25,5		●●●●●●●●	78,0	100mt.
PUES 1209	12x9	+0,15-0,15	35	7,0	21,0		●●●●●●●●	61,0	100mt.
PUES 1410	14x10	+0,15-0,15	45	8,0	24,0		●●●●●●●●	108,0	50mt.
PUES 1612	16x12	+0,15-0,15	60	8,5	25,5		●●●●●●●●	122,0	50mt.

Shore98A