



BRASS PUSH-IN FITTINGS


MADE IN ITALY





 **TierreGroup**[®]
INDUSTRIAL AUTOMATION
HYGIENIC & FOOD FOOD & BEVERAGE

 **NET.Fit**[®]

 **TierreFittings**[®]

 **INOX.Fit**[®]

 **F-Line**[®]



BRASS PUSH-IN FITTINGS

PLUS

HIGH PERFORMANCE FITTINGS,
easy to be used.

STRONG but also compact in order to
ensure the maximum assembling flexibility.

SILICON FREE MATERIALS.

IN COMPLIANCE WITH ISO 14743.

COMPLETE RANGE suitable to be used
with different kind of tubing.

ELECTROLYTIC NICKEL PLATING
to ensure the maximum lasting in time.

**SUITABLE WITH VACUUM
APPLICATIONS.**

STATIC GRIPPING SYSTEM in order
to stop all the movements of the tube
when inserted, granting **A LEAK-PROOF
CONNECTION.**


Every fitting is **STUDIED TO
GUARANTEE THE MAXIMUM
POSSIBLE FLOW RATE** accordingly to
the diameter of the tube and of the thread.

O-RING WITH ENLARGED SECTION
to improve the gripping and the resistance
to vibrations and lateral movements of the
tube.

M A D E I N I T A L Y



p. 7 / **OTRC-R**p. 7 / **OTRC-G**p. 8 / **OTRC-N**p. 8 / **OTROC-N**p. 8 / **OTRMM**p. 9 / **OTRME**p. 9 / **OTRL-R**p. 9 / **OTRL-G**p. 10 / **OTRL-N**p. 10 / **OTRT-R**p. 11 / **OTRT-G**p. 11 / **OTRT-N**p. 12 / **OTA-G**p. 12 / **OTRUC**p. 12 / **OTRUC-N**p. 13 / **OTRUL**p. 13 / **OTRUL-N**p. 13 / **OTRUT**p. 13 / **OTRUT-N**p. 14 / **OTRGJ**



-20°C ÷ 80°C



Working pressure:
16 Bar

Negative pressure:
-750 mmHg



Compressed air and vacuum.



Taper gas BSPT ISO 7
from R1/8" to R1/2"
Parallel gas BSPP ISO 228
from G1/8" to G1/2"
Metric ISO 262 M5 and M7
NPT ANSI B 1.20.1
from N1/8" to N1/2"
UNF ANSI B 1.1 10-32 UF



Polyamide, Polyurethane,
Polyethylene



Body: nickel plated brass
UNI EN 12164 CW614N & UNI
EN 12164 CW617N

Collar: POM

Collet (sleeve): nickel plated brass
UNI EN 12164 CW614N

Seals: NBR silicon free

Lock claw: AISI 301 stainless steel

Back ring: PBT

Retaining ring for swivel systems:
AISI 302 stainless steel





Products in compliance with
the directive 2002/95/EC

RoHS2

Products in compliance with
the directive 2011/65/EU

SILICON FREE

CONSTRUCTION MATERIALS




INSERTION OF THE TUBE INTO THE FITTING

- Make sure the tube is fully inserted into the fitting.
- To insert the tube into the fitting cut the tube at a squared angle (90°), insert up to the end and pull gently to make sure it is correctly connected.
- If there are any damages or scratches on the tube surface or an oval shape, air leakage and tube release may occur. Check it carefully.
- The OD of polyurethane tubes expand when pressure is applied. Reinsertion into the fitting may not be possible. Check the OD of the tube and change the tube if the expansion is serious.
- Always remove by cutting the part of the tube previously inserted into the fitting. Use a proper tube cutter in order to cut the tube.

DISCONNECTION OF THE TUBE FROM THE FITTING

- Make sure the pressure is zero before releasing the tube from the fitting.
- To release the tube, press the release ring regularly at the end and pull the tube with one hand.



TOLERANCE - METRIC TUBE

TUBES Ø	Ø 4 mm	Ø 6 mm	Ø 8 mm	Ø 10 mm	Ø 12 mm
TOLERANCES (mm)	± 0,1	± 0,1	± 0,1	± 0,15	± 0,15

TOLERANCE - INCH TUBE

TUBES Ø	Ø 5/32	Ø 5/16	Ø 1/4	Ø 3/8	Ø 1/2
TOLERANCES (INCH)	±0,004	±0,004	±0,004	± 0,006	± 0,006


INSERTION - METRIC TUBE

DIAMETER TUBES Ø	Ø 4 mm	Ø 6 mm	Ø 8 mm	Ø 10 mm	Ø 12 mm
TUBES INSERTION LENGHT (mm)	14	15,5	17,5	19	21


INSERTION - INCH TUBE

DIAMETER TUBES Ø	Ø 5/32	Ø 5/16	Ø 1/4	Ø 3/8	Ø 1/2
TUBES INSERTION LENGHT (INCH)	0,551	0,688	0,629	0,728	0,846




OTRC-R**Male connector internal hexagonal BSPT thread nickel plated**

CODE	ØD	T	ØP	I	L	CH	H	GR.
OTRC04R01	4	R1/8"	10	8	18,5	10	3	7,0
OTRC04R02		R1/4"	10	10	20	14	3	15,0
OTRC06R01	6	R1/8"	12	8	21	12	4	9,0
OTRC06R02		R1/4"	12	10	20	14	4	14,0
OTRC08R01	8	R1/8"	14	8	26	14	5	15,0
OTRC08R02		R1/4"	14	10	24	14	6	14,0
OTRC08R03		R3/8"	14	11	22	17	6	24,0
OTRC10R02	10	R1/4"	16	10	31	16	6	22,0
OTRC10R03		R3/8"	16	11	26	17	8	23,0
OTRC10R04		R1/2"	16	14	26,5	22	8	45,0
OTRC12R02	12	R1/4"	19	10	33	19	6	21,0
OTRC12R03		R3/8"	19	11	29,5	19	10	27,0
OTRC12R04		R1/2"	19	14	27	22	10	44,5

OTRC-G**Male connector internal hexagonal BSPP & metric thread nickel plated**

CODE	ØD	T	ØC	ØP	I	L	CH	H	GR.
OTRC04M5	4	M5X0,8	7	10	4	19	9	2,5	5,0
OTRC04G01		G1/8"	14	10	5,5	18	10	3	8,0
OTRC04G02		G1/4"	16	10	6,5	18	10	3	11,0
OTRC06M5	6	M5X0,8	7	12	4	21	11	2,5	8,0
OTRC06G01		G1/8"	14	12	5,5	19,5	12	4	9,0
OTRC06G02		G1/4"	16	12	6,5	19,5	12	4	12,0
OTRC08G01	8	G1/8"	14	14	5,5	24,5	14	5	14,0
OTRC08G02		G1/4"	16	14	6,5	21,5	14	6	13,5
OTRC08G03		G3/8"	20	14	7,5	21,5	14	6	20,0
OTRC10G02	10	G1/4"	16	16	6,5	27,5	16	6	19,0
OTRC10G03		G3/8"	20	16	7,5	25	16	8	22,0
OTRC10G04		G1/2"	25	16	9	25	16	8	33,0
OTRC12G02	12	G1/4"	16	19	6,5	30	19	6	28,0
OTRC12G03		G3/8"	22	19	7,5	29,5	19	10	30,0
OTRC12G04		G1/2"	25	19	9	28	19	10	37,0


OTRC-N



Male connector internal hexagonal NPT thread nickel plated

CODE	ØD	T	ØP	I	L	CH	H	GR.
OTRC532N01	5/32"	N1/8"	0,393	0,334	0,748	7/16"	1/8"	9,0
OTRC532N02		N1/4"	0,393	0,413	0,787	9/16"	1/8"	16,0
OTRC1-4N01	1/4"	N1/8"	0,511	0,334	0,885	1/2"	3/16"	11,0
OTRC1-4N02		N1/4"	0,511	0,413	0,885	9/16"	3/16"	15,0
OTRC516N01	5/16"	N1/8"	0,551	0,334	1,062	9/16"	3/16"	15,5
OTRC516N02		N1/4"	0,551	0,413	1,003	9/16"	1/4"	16,0
OTRC516N03		N3/8"	0,551	0,452	0,925	11/16"	1/4"	25,0
OTRC38N01	3/8"	N1/8"	0,629	0,334	1,122	11/16"	3/16"	21,5
OTRC38N02		N1/4"	0,629	0,413	1,181	11/16"	1/4"	25,0
OTRC38N03		N3/8"	0,629	0,452	1,003	11/16"	5/16"	24,0
OTRC38N04		N1/2"	0,629	0,570	1,043	7/8"	5/16"	46,0
OTRC1-2N02	1/2"	N1/4"	0,748	0,413	1,318	7/8"	1/4"	37,0
OTRC1-2N03		N3/8"	0,748	0,452	1,338	7/8"	3/8"	39,0
OTRC1-2N04		N1/2"	0,748	0,570	1,181	7/8"	3/8"	43,0


OTROC-N



Male connector internal hexagon UNF thread nickel plated

CODE	ØD	T	ØP	I	L	H	GR.
OTROC532UF1032	5/32"	UNF 10-32	0,393	0,157	0,748	3/32"	12,0
OTROC1-4UF1032	1/4"	UNF 10-32	0,511	0,157	0,846	3/32"	16,0

OTRMM




Bulkhead connector nickel plated

CODE	ØD	T	ØP	L	I MAX	CH	GR.
OTRMM04-532	4	M12X1	10	34	15	16	23,0
OTRMM0600	6	M14X1	12	32	12	17	31,0
OTRMM08-516	8	M16X1	14	36,5	16	19	36,0
OTRMM1000	10	M20X1	16	43	19	24	70,0
OTRMM1200	12	M22X1,5	19	44	20	25	76,0



OTRME


Male elbow BSPT thread nickel plated



CODE	ØD	T	ØP	I	L1	L2	GR.
OTRME04R01	4	R1/8"	10	8	18	15,5	11,0
OTRME06R01	6	R1/8"	12	8	19,5	15,5	15,0
OTRME06R02		R1/4"	12	10	20,5	19,25	25,0
OTRME08R01	8	R1/8"	14	8	22,5	16,5	20,0
OTRME08R02		R1/4"	14	10	22,5	19,25	24,0
OTRME10R02	10	R1/4"	16	10	25,5	20,5	26,0

OTRL-R


Swivel male elbow BSPT thread nickel plated



CODE	ØD	T	ØP	I	L1	L2	CH	GR.
OTRLO4R01	4	R1/8"	10	8	19,5	20,5	13	20,0
OTRLO4R02		R1/4"	10	10	19,5	23	14	23,0
OTRLO6R01	6	R1/8"	12	8	21	20,5	13	20,0
OTRLO6R02		R1/4"	12	10	21	23	14	24,0
OTRLO8R01	8	R1/8"	14	8	23	20,5	13	22,0
OTRLO8R02		R1/4"	14	10	23	23	14	26,0
OTRLO8R03		R3/8"	14	11	23	24,5	17	32,0
OTRL10R02	10	R1/4"	16	10	26	25,5	16	41,0
OTRL10R03		R3/8"	16	11	26	27	17	45
OTRL10R04		R1/2"	16	14	26	30	22	59,0
OTRL12R02	12	R1/4"	19	10	31	28	20	56,0
OTRL12R03		R3/8"	19	11	31	28,5	20	59,0
OTRL12R04		R1/2"	19	14	31	31,5	22	70,0

OTRL-G

Swivel male elbow BSPP & metric nickel plated




CODE	ØD	T	ØP	ØC	I	L1	L2	CH	GR.
OTRLO4M5	4	M5X0,8	10	7	4	18	15	8	5,0
OTRLO4G01		G1/8"	10	13	5,5	19,5	19	13	19,0
OTRLO4G02		G1/4"	10	16	6,5	19,5	21,5	13	22,0
OTRLO6M5	6	M5X0,8	12	7	4	19,5	16	8	11,0
OTRLO6G01		G1/8"	12	13	5,5	21	19	13	20,0
OTRLO6G02		G1/4"	12	16	6,5	21	21,5	13	24,0
OTRLO8G01	8	G1/8"	14	13	5,5	23	19	13	22,0
OTRLO8G02		G1/4"	14	16	6,5	23	21,5	13	24,0
OTRLO8G03		G3/8"	14	20	7,5	23	23	13	28,0
OTRL10G02	10	G1/4"	16	16	6,5	26	23	16	35,0
OTRL10G03		G3/8"	16	20	7,5	26	26	16	43,5
OTRL10G04		G1/2"	16	25	9	26	27,5	16	52,0
OTRL12G02	12	G1/4"	19	16	6,5	31	25,5	20	55,0
OTRL12G03		G3/8"	19	20	7,5	31	26,5	20	55,0
OTRL12G04		G1/2"	19	25	9	31	29	20	63,0



OTRL-N


Swivel male elbow NPT & UNF thread nickel plated



CODE	ØD	T	E	I	L	CH	GR.
OTRL532UF1032	5/32"	UNF 10/32	0,708	0,157	0,590	3/8"	11,0
OTRL532N01		N1/8"	0,767	0,334	0,826	9/16"	20,5
OTRL532N02		N1/4"	0,767	0,413	0,925	9/16"	24,0
OTRL1-4N01	1/4"	N1/8"	0,826	0,334	0,826	9/16"	23,0
OTRL1-4N02		N1/4"	0,857	0,413	0,925	9/16"	26,0
OTRL516N01	5/16"	N1/8"	0,905	0,334	0,826	9/16"	23,0
OTRL516N02		N1/4"	0,905	0,413	0,925	9/16"	24,0
OTRL516N03		N3/8"	0,905	0,452	0,984	11/16"	34,0
OTRL38N01	3/8"	N1/8"	1,003	0,334	0,944	11/16"	40,0
OTRL38N02		N1/4"	1,003	0,413	1,023	11/16"	43,0
OTRL38N03		N3/8"	1,023	0,452	1,082	11/16"	47,0
OTRL38N04		N1/2"	1,003	0,570	1,200	7/8"	60,0
OTRL1-2N02	1/2"	N1/4"	1,220	0,413	1,122	7/8"	58,0
OTRL1-2N03		N3/8"	1,220	0,452	1,161	7/8"	61,0
OTRL1-2N04		N1/2"	1,220	0,570	1,279	7/8"	67,0


OTRT-R

Swivel male tee BSPT thread nickel plated




CODE	ØD	T	ØP	I	E	L	CH	GR.
OTRT04R01	4	R1/8"	10	8	21	39	13	27,0
OTRT04R02		R1/4"	10	10	23,5	39	14	31,0
OTRT06R01	6	R1/8"	12	8	21	42	13	30,0
OTRT06R02		R1/4"	12	10	23,5	42	14	34,0
OTRT08R01	8	R1/8"	14	8	21	46,5	13	34,0
OTRT08R02		R1/4"	14	10	23,5	46,5	14	37,0
OTRT08R03		R3/8"	14	11	25	46,5	17	44,0
OTRT10R02	10	R1/4"	16	10	25,5	52	16	55,0
OTRT10R03		R3/8"	16	11	27	52	17	58,5
OTRT10R04		R1/2"	16	14	30	52	22	73,0
OTRT12R02	12	R1/4"	19	10	28	62	20	77,0
OTRT12R03		R3/8"	19	11	28,5	62	20	80,0
OTRT12R04		R1/2"	19	14	31,5	62	22	81,0



OTRT-G**Swivel male tee BSPP & metric thread nickel plated**

CODE	ØD	T	ØP	I	E	L	CH	GR.
OTRT04M5	4	M5X0,8	10	4	17	32	8	17,0
OTRT04G01		G1/8"	10	5,5	19,5	39	13	29,0
OTRT04G02		G1/4"	10	6,5	22	39	13	29,0
OTRT06M5	6	M5X0,8	12	4	17	40	8	21,0
OTRT06G01		G1/8"	12	5,5	19,5	42	13	29,0
OTRT06G02		G1/4"	12	6,5	22	42	13	32,0
OTRT08G01	8	G1/8"	14	5,5	19,5	46,5	13	33,0
OTRT08G02		G1/4"	14	6,5	22	46,5	13	35,5
OTRT08G03		G3/8"	14	7,5	23,5	46,5	13	39,0
OTRT10G02	10	G1/4"	16	6,5	23	52	16	52,0
OTRT10G03		G3/8"	16	7,5	26	52	16	56,0
OTRT10G04		G1/2"	16	9	27,5	52	16	64,5
OTRT12G02	12	G1/4"	19	6,5	25,5	62	20	75,0
OTRT12G03		G3/8"	19	7,5	26,5	62	20	77,0
OTRT12G04		G1/2"	19	9	29	62	20	82,0


OTRT-N**Swivel male tee NPT & UNF thread nickel plated**

CODE	ØD	T	ØP	I	E	L	CH	GR.
OTRT532UF1032	5/32"	UNF 10-32	0,393	0,157	0,669	1,259	3/8"	17,0
OTRT532N01		N1/8"	0,393	0,334	0,846	1,535	9/16"	28,0
OTRT532N02		N1/4"	0,393	0,413	0,944	1,535	9/16"	31,0
OTRT1-4N01	1/4"	N1/8"	0,551	0,334	0,846	1,673	9/16"	33,0
OTRT1-4N02		N1/4"	0,551	0,413	0,944	1,673	9/16"	36,0
OTRT516N01	5/16"	N1/8"	0,551	0,334	0,846	1,830	9/16"	34,0
OTRT516N02		N1/4"	0,551	0,413	0,944	1,830	9/16"	37,0
OTRT38N02	3/8"	N1/4"	0,649	0,413	1,023	2,027	11/16"	58,0
OTRT38N03		N3/8"	0,649	0,452	1,082	2,027	11/16"	61,0
OTRT1-2N02	1/2"	N1/4"	0,767	0,413	1,122	2,440	7/8"	75,0
OTRT1-2N03		N3/8"	0,767	0,452	1,161	2,440	7/8"	78,0



OTA-G


Stem adapter BSPP & metric thread nickel plated



CODE	ØD	T	DN	ØP	ØC	I	L	H	GR.
OTA04M5	4	M5	2,0	8,0	2,0	4,0	24,5	8	3,0
OTA04M7		M7	2,0	-	4,0	6,0	26,0	10	5,0
OTA04G01		G1/8"	2,0	13,0	6,0	6,0	28,0	13	10,0
OTA04G02		G1/4"	2,0	16,0	7,5	8,0	30,0	13	11,0
OTA06M5	6	M5	2,6	8,0	2,6	4,0	26,0	8	5,0
OTA06M7		M7	4,0	-	4,0	6,0	28,0	10	7,0
OTA06G01		G1/8"	4,0	13,0	6,0	6,0	29,5	13	9,0
OTA06G02		G1/4"	4,0	16,0	7,5	8,0	32,0	13	13,0
OTA08G01	8	G1/8"	6,0	13,0	6,0	6,0	31,0	13	10,0
OTA08G02		G1/4"	6,0	16,0	7,5	8,0	33,5	13	13,0
OTA08G03		G3/8"	6,0	20,0	9,0	9,0	35,5	13	21,0
OTA10G01	10	G1/8"	6,0	13,0	6,0	6,0	35,5	13	17,0
OTA10G02		G1/4"	8,0	16,0	8,0	8,0	38,0	13	15,0
OTA10G03		G3/8"	8,0	20,0	8,0	9,0	41,0	13	26,0
OTA12G02	12	G1/4"	8,0	16,0	8,0	8,0	39,0	13	22,0
OTA12G03		G3/8"	10,0	20,0	11,0	9,0	42,0	13	22,0
OTA12G04		G1/2"	10,0	24,0	13,0	11,0	44,0	16	35,0

OTRUC


Union connector metric tube nickel plated



CODE	ØD	ØP	L	GR.
OTRUC04-532	4	10	29	9,0
OTRUC0600	6	12	32	12,0
OTRUC08-516	8	14	35,5	16,0
OTRUC1000	10	16	39,5	21,0
OTRUC1200	12	19	44	37,0

OTRUC-N

Union connector inch tube nickel plated




CODE	ØD	ØP	L	GR.
OTRUC04-532	5/32"	0,393	1,141	9,0
OTRUC1-4	1/4"	0,511	1,299	14,0
OTRUC08-516	5/16"	0,551	1,397	16,0
OTRUC38	3/8"	0,629	1,515	21,0
OTRUC1-2	1/2"	0,748	1,732	37,0



OTRUL


Union elbow metric tube nickel plated



CODE	ØD	ØP	L	GR.
OTRUL04-532	4	10	18	12,0
OTRUL0600	6	12	19,5	14,0
OTRUL08-516	8	14	22,5	20,0
OTRUL1000	10	16	25,5	26,0
OTRUL1200	12	19	29	49,0

OTRUL-N


Union elbow inch tube nickel plated



CODE	ØD	ØP	L	GR.
OTRUL04-532	5/32"	0,393	0,708	12,0
OTRUL1-4	1/4"	0,551	0,826	19,0
OTRUL08-516	5/16"	0,551	0,885	20,0
OTRUL38	3/8"	0,649	0,984	28,0
OTRUL1-2	1/2"	0,767	1,122	43,0

OTRUT


Union tee metric tube nickel plated



CODE	ØD	ØP	E	L	GR.
OTRUT04-532	4	10	18	36	17,0
OTRUT0600	6	12	19,5	39	20,0
OTRUT08-516	8	14	22,5	45	30,0
OTRUT1000	10	16	25,5	51	37,0
OTRUT1200	12	19	29	58	68,0

OTRUT-N


Union tee inch tube nickel plated



CODE	ØD	ØP	E	L	GR.
OTRUT04-532	5/32"	0,393	0,708	1,417	16,9
OTRUT1-4	1/4"	0,551	0,826	1,633	26,8
OTRUT08-516	5/16"	0,551	0,885	1,771	29,7
OTRUT38	3/8"	0,649	0,984	1,988	38,3
OTRUT1-2	1/2"	0,767	1,122	2,263	58,7



OTRGJ



Stem reduction metric tube nickel plated

CODE	ØD1	ØD2	ØP	L1	L2	GR.
OTRGJ0604	6	4	10	19,50	31	6,0
OTRGJ0806	8	6	12	21,50	34,50	8,0
OTRGJ1008	10	8	14	22,50	36,50	13,0
OTRGJ1210	12	10	16	25,0	40,50	18,0





Tierre Group S.p.a.

via dell'Industria, 18 - 20032 Cormano (MI)

Tel. +39 02 663088.1 - Fax +39 02 66304172

www.tierregroup.com - info@tierregroup.com

C.F. e P.IVA 12437570158

Cap. Soc. Euro 120.000,00 i.v. - REA MI-1558390

Brass Push-In Fittings Catalogue - Ed. 1.0 - 04/18