

PUSH-ON FITTINGS

PVDF

PLUS

**GREAT GRIPPING SYSTEM WITH
THE LOCKING NUT**

GREAT TEMPERATURE RANGE


**EASY TO BE USED AND EXTREMELY
STRONG**

**VERY STRONG RESISTANT FROM TUBE
PULL OUT**

HIGH CORROSIVE CHEMICALS



p. 194 / **2900**p. 194 / **2905**p. 194 / **2910**p. 195 / **2915**p. 195 / **2930**p. 195 / **2935**p. 195 / **2940**p. 196 / **2950**p. 196 / **2955**p. 196 / **2960**p. 196 / **2965**p. 197 / **2970**p. 197 / **2230**



-20°C ÷ +120°C
Subject to applications



Up to 14 Bar at 20°C



Compressed air, water and fluids
suitable with construction materials



Taper gas BSPT ISO 7
from R1/8" to R3/4"



Polyurethane, Polyethylene,
Polyamide, PTFE , FEP

PRECAUTIONS

- The products are made in plastic and it's necessary to use teflon coating over the thread for installation in order and to prevent air leakage.
Be sure to prevent excessive torque when screwing the fittings.
- To connect the tube, insert the tube to the end and tight the cap before use.
- Cut the pressed part of the tube before connection to reuse the released tube



Body: Polyvinylidene flouride (PVDF)
Lock nut: Polypropylene
O'ring: Silicon

Available on demand
also for inch size & NPT thread



Products in compliance with
the directive 2002/95/EC

RoHS2

Products in compliance with
the directive 2011/65/EU



RECOMMENDED
TIGHTENING TORQUE

THREAD SIZE	NM	FT LB
1/8	0,1	0,07
1/4	1	0,8
3/8	5	3
1/2	8	6
3/4	16	12


MEASURES BARB

Ø	MM
Ø6	6,2
Ø8	7,2
Ø10	9,2
Ø12	12



2900


Male connector BSPP thread with O-Ring



CODE	ØD	T	L	GR.
2900TR186	6/4	G1/8"	27,2	4,14
2900TR146	6/4	G1/4"	30,9	5,37
2900TR188	8/5,5	G1/8"	27,3	4,09
2900TR148	8/5,5	G1/4"	31,1	5,9
2900TR1810	10/7	G1/8"	27,2	-
2900TR1410	10/7	G1/4"	31,0	-

2905


Female connector BSPT thread



CODE	ØD	T	I	L	H1	H2	GR.
2905TR186	6/4	R1/8"	10,0	26,3	14	14	3,0
2905TR146	6/4	R1/4"	11,0	28,0	14	17	3,0
2905TR188	8/5,5	R1/8"	9,0	26,3	14	14	3,0
2905TR148	8/5,5	R1/4"	11,0	28,0	14	17	4,0
2905TR388	8/5,5	R3/8"	11,2	30,5	14	22	5,0
2905TR128	8/5,5	R1/2"	13,5	32,5	14	26	6,0
2905TR1410	10/7	R1/4"	10,0	32,0	17	17	6,0
2905TR3810	10/7	R3/8"	11,0	33,5	17	22	7,0
2905TR1210	10/7	R1/2"	13,8	35,5	17	26	7,0

2910

Male connector BSPT thread




CODE	ØD	T	I	L	H1	H2	GR.
2910TR186	6/4	R1/8"	8,0	27,0	14	13	3,0
2910TR146	6/4	R1/4"	10,5	30,0	14	15	3,0
2910TR386	6/4	R3/8"	10,5	27,0	14	18	6,48
2910TR126	6/4	R1/2"	13,0	31,5	14	22	6,0
2910TR346	6/4	R3/4"	9,0	23,0	14	27	8,0
2910TR188	8/5,5	R1/8"	8,0	27,0	14	13	3,0
2910TR148	8/5,5	R1/4"	10,5	30,0	14	15	3,0
2910TR388	8/5,5	R3/8"	10,5	31,5	14	18	4,0
2910TR128	8/5,5	R1/2"	13,0	34,0	14	22	5,0
2910TR348	8/5,5	R3/4"	9,0	27,5	14	27	8,0
2910TR1410	10/7	R1/4"	10,5	36,0	17	17	4,0
2910TR3810	10/7	R3/8"	10,5	36,0	17	17	5,0
2910TR1210	10/7	R1/2"	12,0	39,0	17	22	6,0
2910TR3410	10/7	R3/4"	13,0	40,0	17	27	6,0
2910TR1412	12/9	R1/4"	10,5	34,0	19	14	6,0
2910TR3812	12/9	R3/8"	10,5	36,0	19	18	7,0
2910TR1212	12/9	R1/2"	12,5	37,0	19	22	7,0
2910TR3412	12/9	R3/4"	13,0	34,0	19	27	15,64



2915


Union connector



CODE	ØD1	ØD2	L	H1	H2	GR.
2915TR6	6/4	6/4	32,5	14	14	4,0
2915TR8	8/5,5	8/5,5	32,5	14	14	4,0
2915TR12	12/9	12/9	40,6	19	18	8,0
2915TR86	8/5,5	6/4	32,5	14	14	4,0

2930


Female elbow BSPT thread



CODE	ØD	T	I	L	H1	H2	GR.
2930TR186	6/4	R1/8"	10,5	19,5	14	9	5,0
2930TR146	6/4	R1/4"	12,3	22,5	14	9	5,0
2930TR148	8/5,5	R1/4"	12,3	22,5	14	9	6,0

2935


Union elbow



CODE	ØD	L	H1	H2	GR.
2935TR6	6/4	23,3	14	8	4,0
2935TR8	8/5,5	23,5	14	8	4,0
2935TR12	12/9	32,0	19	15	10,0

2940

Male elbow BSPT thread




CODE	ØD	T	I	L1	L2	H1	H2	GR.
2940TR186	6/4	R1/8"	8,0	18,5	22,5	14	8	2,0
2940TR146	6/4	R1/4"	10,0	23,0	22,5	14	8	3,0
2940TR188	8/5,5	R1/8"	8,5	18,5	23,0	14	8	3,0
2940TR148	8/5,5	R1/4"	11,0	23,0	23,0	14	8	3,0
2940TR388	8/5,5	R3/8"	11,0	23,5	23,0	14	8	5,0
2940TR1412	12/9	R1/4"	10,0	24,0	33,0	19	15	7,0
2940TR3812	12/9	R3/8"	10,0	24,5	33,0	19	15	6,0
2940TR1212	12/9	R1/2"	13,0	28,5	33,0	19	15	9,0



2950


Tee female BSPT thread



CODE	ØD	T	I	L	H1	H2	GR.
2950TR186	6/4	R1/8"	10,2	23,3	14	8	8,16
2950TR148	8/5,5	R1/4"	12,5	23,3	14	8	8,7

2955


Male tee BSPT thread



CODE	ØD	T	I	L1	L2	H1	H2	GR.
2955TR186	6/4	R1/8"	9,0	19,0	23,3	14	8	6,0
2955TR146	6/4	R1/4"	11,0	21,0	23,3	14	8	6,0
2955TR188	8/5,5	R1/8"	9,0	19,0	23,3	14	8	5,0
2955TR148	8/5,5	R1/4"	11,0	21,0	23,3	14	8	6,0
2955TR388	8/5,5	R3/8"	11,0	21,0	23,3	14	8	7,0
2955TR1412	12/9	R1/4"	11,0	21,0	23,3	14	8	12,0
2955TR3812	12/9	R3/8"	10,7	24,5	33,5	19	15	14,0
2955TR1212	12/9	R1/2"	15,0	28,5	33,0	19	15	15,0

2960


Lateral male tee BSPT thread



CODE	ØD	T	I	L	H1	H2	GR.
2960TR186	6/4	R1/8"	8,5	23,3	14	8	5,0
2960TR146	6/4	R1/4"	11,0	23,3	14	8	5,0
2960TR188	8/5,5	R1/8"	8,5	23,3	14	8	5,0
2960TR148	8/5,5	R1/4"	11,0	23,3	14	8	5,0
2960TR388	8/5,5	R3/8"	10,0	23,3	14	8	7,0
2960TR1412	12/9	R1/4"	10,0	33,0	19	15	12,0
2960TR3812	12/9	R3/8"	11,0	33,0	19	15	14,0
2960TR1212	12/9	R1/2"	15,0	33,0	19	15	15,0

2965

Union tee




CODE	ØD1	ØD2	L	L1	H1	H2	GR.
2965TR6	6/4	6/4	22,0	27,5	14	8	7,0
2965TR8	8/5,5	8/5,5	22,0	27,5	14	8	5,0
2965TR12	12/9	12/9	32,0	40,4	19	14	14,0
2965TR68	6/4	8/5,5	46,8	27,4	-	-	8,73
2965TR86	8/5,5	6/4	46,8	27,4	-	-	8,96



2970

Lateral tee male BSPT thread



CODE	ØD	T1	T2	L	L1	GR.
2970TR148	8/5,5	R1/4"	R1/8"	46,2	22,6	7,15

2230

Locking nut



CODE	ØD	ØC	H	GR.
2230TR6	6/4	6,2	14	1,0
2230TR8	8/5,5	8,1	14	2,0
2230TR10	10/7	10,2	17	3,0
2230TR12	12/9	12,8	19	4,0



