

TUBES

FLEXLOCK TUBE

PLUS

**VERY FLEXIBLE
EVEN AT LOW TEMPERATURE**

SILICON FREE

**INNER HOSE MADE OF IMPREVOIUS
BLACK SYNTHETIC RUBBER**





From -50°C to +120°C



Working: 20 Bar
Burst: 60 Bar



Products in compliance with the directive 2002/95/EC

RoHS2

Products in compliance with the directive 2011/65/EU

Caucho FLEXLOCK tube is produced with high quality synthetic raw material and textile reinforcement, without using any kind of plastic.

Caucho tube maintain a very good flexibility even at low temperatures, unlike all those standard tubes which, at low pressure, become rigid. Thanks to the materials which is made of, this tube results very light and easy to handle.

It's fireproof and welding sparks resistant and can work close to sources of heat. It can transport fluids like compressed air, oxygen, acid and gas.

It's suitable for all the applications which require an intensive use of the tube, in automation, robotics plants and in industrial applications in general. It supports the weight of a car lift.

This tube is a good alternative to all the other tubes normally used in the above mentioned applications, especially the common rubber tube for air.

CAU

Caucho light blue tube



CODE	SIZES	PRESSURE OF USING	BURST PRESSURE	BENDING RADIUS	GR./MT.	MT.
CAU0613	6X13	20	60	35	200	50
CAU0815	8X15	20	60	45	250	50
CAU1018	10X18	20	60	70	300	50
CAU1220	12X20	20	60	80	400	50
CAU1525	15X25	20	60	100	550	50
CAU1930	19X30	20	60	150	700	50
CAU2538	25X38	20	60	160	840	50

